



IP 44, NEMA 12, IK 10

**Multi-purpose IP 44 computer enclosure in attractive two-tone colour (RAL 7035 & RAL 7015), is suitable for office and factory environments. The rigid construction offers suitable protection against many adverse conditions and theft, while the clever design quickens installation and offers multiple mounting options. MCM is delivered complete with monitor shelf. Non-standard colours are available on request.**

**Material:** Frame: 1.5mm steel plate. Roof and side panels: 1.35mm steel plate. Doors: 2mm steel plate. Bottom plates: 1mm galvanized steel.

**Frame:** Seam welded reversed open profiles with 25mm hole pattern according to double-bit 3mm 43660. Including integrated external hole pattern.

**Door:** Mounted with two hinges per door. Top door with safety glass. Viewing area for 14"- 21" monitor.

**Rear door:** Mounted with hinges allowing left or right hand opening. Including door frame with 25mm hole pattern.

**Keyboard panel:** Vertical opening keyboard panel. Sliding mouse pad allowing left or right hand use. Max keyboard dimensions 470 mm x 190 mm x 45 mm.

**Lock:** Espagnolette 4 point locking system. Standard double-bit lock with 3mm pin. Can be exchanged for standard inserts or Euro-cylinder and swing handle.

**Bottom plates:** Consists of three or four (D> 600) pieces.

**Finish:** Two tone finish. Doors, side panels, roof and frame in RAL 7035 structured powder coating. Keyboard side panels and monitor door pane in RAL 7015 structured powder coating. Other colour schemes optional.

**Features:** Special design of roof and side panels for theft security. All panels are only accessible when the doors are unlocked. Your own company name can be inserted in the top plinth (option).

**Protection:** Complies with IP 44, NEMA 12, IK 10. With keyboard tray opened corresponding with IP 30.

**Delivery:** Frame with fitted rear door, side panels, roof panel, monitor door, keyboard panel, bottom plates and monitor shelf with clamps to fix the monitor. Delivery also includes earthing bolts. The enclosure is delivered on a pallet identical to the enclosure width. All packing material is recyclable.

**Mounting requirement:** Equipment shelves need to be added.

| Enclosure dimension |     |     |          |  |
|---------------------|-----|-----|----------|--|
| H                   | W   | D   | Part No. |  |
| 1600                | 600 | 600 | MCM16066 |  |
| 1600                | 600 | 800 | MCM16068 |  |

